

AMENDED CLAIM SET

The claims have been amended as follows:

1. (canceled)
2. (currently amended) An inflator according to claim 13, wherein the single rupturable plate and the igniter are arranged such that an imaginary central axis of the single rupturable plate that penetrates a center of the single rupturable plate and an imaginary central axis of the actuating portion of the igniter towards which the output is discharged are coincident with each other.
3. (currently amended) An inflator according to claim 13, wherein the gas introducing chamber directs a flow of the pressurized gas along a longitudinal axial direction of the cylindrical inflator housing, and the igniter accommodating chamber directs the flow of the pressurized gas along a direction orthogonal to the longitudinal axial direction of the inflator housing,

wherein a center of the second opening ~~portion~~ coincides with a center of the third opening ~~portion~~.
4. (currently amended) An inflator according to claim 13, ~~further comprising:~~

wherein, the single rupturable plate is a cylindrical cup inserted into the gas introducing chamber through the first opening ~~portion~~, such that a side wall of the cylindrical cup opposes and closes the second opening ~~portion~~ and closes the gas discharging passage.
5. (canceled)

6. (currently amended) An inflator according to claim 13, further comprising:
a cylindrical retainer for holding ~~the an~~ igniter therein and adapted to be inserted into the igniter accommodating chamber through the third opening,
~~wherein, the single ; and~~
~~— a rupturable plate is attached to one end of the cylindrical retainer prior to an insertion of the cylindrical retainer through into the third opening, such that the single rupturable plate closes the second opening once the cylindrical retainer is inserted into the igniter accommodating chamber third opening.~~

7. (currently amended) An inflator according to claim 13, further comprising:
an annular fixture defining a central hole and adapted to be inserted into the ignition accommodating chamber through the third opening ~~portion~~,
wherein the single rupturable plate is fixed to the annular fixture to cover the central hole, such that single the rupturable plate is sandwiched between the annular fixture and a surface defining the second opening ~~portion~~ to close the second opening ~~portion~~ once the annular fixture is inserted into the igniter ~~ignition~~ accommodating chamber.

8. (currently amended) An inflator according to claim 13, wherein the diffuser portion is provided with a fourth opening communicating with the gas introducing chamber for inserting the single rupturable plate into the gas introducing chamber through the fourth opening, and a lid is provided to close the fourth opening.

9. (previously presented) An inflator according claim 13, wherein the igniter is mounted in the ignition accommodating chamber, the inflator further comprising:

a lead wire connected to the igniter via a connector for transmitting an operation signal to the igniter,

wherein the lead wire extends in a direction perpendicular to an imaginary center axis of the second opening.

10. (currently amended) An inflator according to claim 13, further comprising:

a cylindrical diffuser housing having a first end defining an opening and a second end which is closed, the cylindrical diffuser housing having, in a peripheral wall thereof, ~~the vicinity of the second end~~ a second gas discharging hole, the first end of the cylindrical diffuser housing being connected to the diffuser ~~portion to cover the gas discharging hole of the diffuser portion~~ and extends along a direction of an imaginary longitudinal central axis of the inflator housing to receive the pressurized gas discharged from the gas discharging hole and discharging the received pressurized gas through ~~from~~ the second gas discharging hole.

11. (currently amended) An inflator according to claim 10, wherein a plurality of second gas discharging holes are formed in ~~on~~ a side wall of the cylindrical diffuser housing at equal intervals.

12. (previously presented) An air bag system comprising:

activation signal-outputting means including an impact sensor and a control unit; and

a module case accommodating an inflator according to claim 13 and an air bag.

13. (currently amended) An inflator, comprising:

a cylindrical inflator housing having a first end that is closed and a second end defining an opening, and adapted to accommodate a pressurized gas therein, the cylindrical inflator housing extending in a longitudinal axial direction thereof;

a diffuser portion attached to the second end of the cylindrical inflator housing, the diffuser portion including,

a gas introducing chamber in communication with the cylindrical inflator housing through a first opening,

an igniter accommodating chamber for accommodating an ~~the~~ igniter and in communication with the gas introducing chamber through a second opening, the igniter accommodating chamber having a third opening, for inserting the ~~an~~ igniter, at a portion opposing the second opening, and

a gas discharging hole provided in a wall of the diffuser portion for discharging the pressurized gas ~~from the igniter accommodating chamber~~, an imaginary center axis of the gas discharging hole being parallel to an imaginary center axis of the first opening, such that the pressurized gas is discharged in a direction parallel to the longitudinal axial direction of the cylindrical inflator housing; the diffuser portion defining therein a gas path extending from the first opening to the gas discharging hole; and

only a single rupturable plate provided within the diffuser portion and blocking which
~~blocks the gas path passage prior to activation of the inflator, the rupturable plate being attached to the diffuser portion from a side closer to the first opening than a side of the igniter.~~

14. (previously presented) An inflator according to claim 13, wherein the second opening is provided such that an imaginary center axis of the second opening is perpendicular to the longitudinal axial direction.

15. (currently amended) An inflator according to claim ~~11~~¹⁴, wherein an air bag is connected to the cylindrical diffuser housing.

16. (previously presented) An inflator according to claim 13, wherein the gas introducing chamber directs a flow of the pressurized gas along an imaginary longitudinal central axis of the inflator housing, and the igniter accommodating chamber directs the flow of the pressurized gas along a direction orthogonal to the imaginary longitudinal central axis of the inflator housing.